

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

KLH® - CLT

according to the product specification listed in the current addendum to this certificate placed on the market

Company

KLH MASSIVHOLZ GMBH

Gewerbestraße 4 AT-8842 Teufenbach-Katsch

and in the manufacturing plants
KLH Massivholz GmbH
AT-8842 Teufenbach-Katsch, Gewerbestraße 4

KLH Massivholz Wiesenau GmbH AT-9462 Bad St. Leonhard, Wiesenau 2

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

ETA-06/0138, issued on 18.01.2021 and

EAD 130005-00-0304

under system 1 for the performance set out in the ETA are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Certificate number: 1359-CPR-0736 Date of first issue: 07.09.2017 Date of issuance: 04.02.2021

This certificate will remain valid as long as neither the ETA, the EAD, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see www.holzforschung.at.

DI Bernhard Kraus

Authorised signatory



Dr. Manfred Brandstätter Head of the Certification Body

HOLZFORSCHUNG AUSTRIA - ÖSTERREICHISCHE GESELLSCHAFT FÜR HOLZFORSCHUNG ZVR 850936522 A-1030 Wien, Franz Grill-Straße 7 Tel +43-1/798 26 23-0 Fax +43-1/798 26 23-50 hfa@holzforschung.at www.holzforschung.at

Addendum to certificate 1359-CPR-0736

Date of issuance: 04.02.2021



Scope of certification:

KLH® - CLT

Solid wood slabs to be used as structural elements in building

Structure:

minimum 3-layers,

layers arranged perpendicular (angle of 90°), maximum 18 layers, symmetrical construction,

Strength classes of the laminations: C 24 according EN 338

Thickness:

57 - 360 mm

Width x length:

max. 3,5 x 16,5 m

Service classes:

1, 2

Wood species:

PCAB - spruce/ ABAL - fir;

PNSY - pine

Adhesive:

- Finger joints

Type I: PUR according to EN 15425

- Surface bonding:

Type I: PUR according to EN 15425