



MADE FOR BUILDING
BUILT FOR LIVING

**OPERATING INSTRUCTIONS
FOR KLH® LIFTING SYSTEMS**



IMPRINT

Version: Operating instructions for KLH® lifting systems, 10/2024

Publisher and responsible for content: © KLH Massivholz GmbH

The content of this brochure is the intellectual property of the company and is protected by copyright.
The statements are recommendations and suggestions only; liability on the part of the publisher is excluded.
Any type of reproduction is strictly forbidden and only permitted after written approval from the publisher.

KLH® and the KLH® logo are internationally registered trademark rights of KLH Massivholz GmbH.
The fact that a mark is not included in the list and/or not indicated as registered trademark (brand)
in a text cannot be interpreted in anyway that this mark is not a registered trademark (brand)
and/or that this mark could be used without prior written acceptance of KLH Massivholz GmbH.



CONTENT

01 UNLOADING, TEMPORARY STORAGE, LIFTING 03

02 GENERAL INFORMATION ON INSTALLING THE ONE-WAY LIFTING LOOPS 04

03 INSTALLATION 07

04 EC CERTIFICATES OF CONFORMITY 08

01 UNLOADING, TEMPORARY STORAGE, LIFTING

GUIDELINE FOR THE USE OF KLH® LIFTING GEAR SYSTEMS WITH EC CERTIFICATE OF CONFORMITY

Lifting operations using KLH® lifting gear systems with an EC certificate of conformity may only be carried out with suitable lifting equipment and a suitable hanger.



Use a high capacity lifting device (minimum diameter 10 mm) in accordance with EN 818-2.

Please observe the following procedure for lifting, unloading, interim storing, and assembling:

- Visually inspect the installed one-way lifting loops
- Hook into all installed lifting loops (hook opening to the outside, please refer to illustration)
- Maximum distance between the lifting points 6 m
- Inclination angle of the hanger $45^\circ - 60^\circ$

TRANSPORT FLAT →
LIFT FLAT
OR
TRANSPORT STANDING →
LIFT STANDING


Unloading and assembling are carried out directly from the trailer using the built-in KLH® lifting gear; the position of the element remains unchanged.



UNLOADING, TEMPORARY STORAGE, LIFTING

TRANSPORT FLAT → TURNING UPRIGHT → LIFT STANDING


The built-in KLH® lifting devices of type „W“ and „VLS W“ are suitable both for turning upright and for lifting the element upright. When turning upright, the elements must be prevented from slipping (direction of pull $\alpha = 110^\circ$). This variant can be used for horizontal delivery of wall elements.




Load securing in accordance with legal regulations and provisions

TRANSPORT STANDING → LAYING DOWN → LIFT FLAT

The element is unloaded and deposited horizontally and securely using the built-in KLH® lifting gear type „W“ or „VLS W“. The hanger must then be transferred to the lifting gear for horizontal lifting (e.g. type „VLS S“). In exceptional cases, the loops supplied must be installed on site in the factory-prepared holes in accordance with the installation instructions. This variant can be used for upright delivery of slab or roof elements.



1. Unloading with the unloading lifting system



2. Assembling with the assembly lifting system


GENERAL INFORMATION ON INSTALLING THE ONE-WAY LIFTING LOOPS

02 GENERAL INFORMATION ON INSTALLING THE ONE-WAY LIFTING LOOPS


The type and position of the lifting equipment is determined and ordered by the customer. It must be coordinated with both the construction site processes and the means of transportation of the delivery, especially if it is necessary to turn upright or flip elements at the place of arrival. Required drill holes must be marked in the element plans and, if necessary, sealed or filled in a suitable manner on site after installation.

The lifting loops are always installed at the factory. In exceptional cases, only the unloading lifting system is installed for upright transportation, and the system components supplied for the assembly lifting system must be installed on site after unloading. It must be ensured that the loops or bolts provided for the respective element are installed in accordance with the following illustrations.

INSTALLATION OF THE LOOPS FOR SYSTEM VLS S



1. Insert the loop and dowel into the hole



2. Transport situation with rolled-up loop in the blind hole



3. Lifting situation with built-in system VLS S

GENERAL INFORMATION ON INSTALLING THE ONE-WAY LIFTING LOOPS

INSTALLATION OF THE LOOPS FOR SYSTEM W



1. Lifting situation with built-in system W

INSTALLATION OF THE LOOPS FOR SYSTEM FD



1. Insert the lifting loop into the hole



2. Feed the loop back through the second hole



3. Pull the loop upwards



4. Lifting situation with built-in system FD (100 mm center distance of the holes at 45° to the grain direction)

GENERAL INFORMATION ON INSTALLING THE ONE-WAY LIFTING LOOPS

INSTALLATION OF THE LOOPS FOR SYSTEM FB



1. Insert the loop into the hole



2. Do not position the loop seam in the area of the bolt or lifting hook



3. Insert the bolt with the safety clip facing downwards and position it accordingly



4. Lifting situation with built-in FB system


INSTALLATION

03 INSTALLATION

VERTICAL ELEMENT INSTALLATION - WALL ELEMENTS


FIX WALL ELEMENT

- Bring the wall into the installation position - ensure that the wall is secured in position



UNHOOK CRANE HOOKS

- Observe the applicable employee protection regulations and other provisions



DISPOSE OF ONE-WAY LIFTING LOOPS

- According to EU waste directive

HORIZONTAL ELEMENT INSTALLATION - SLAB AND ROOF ELEMENTS

FIX SLAB/ROOF ELEMENT

- Bring the slab/roof element into the installation position - ensure that the element is secured in position

UNHOOK CRANE HOOKS

- When accessing the slab or roof element, observe the applicable employee protection regulations and other provisions



CUT THE LIFTING LOOPS WHEN USING THE VLS SYSTEM

- Wearing safety gloves and using a safety knife in accordance with the Employee Protection Ordinance



EC CERTIFICATES OF CONFORMITY

DECLARATION of CONFORMITY

accord. Directive of Machinery 2006/42/EG

The Signee: *Dipl.-Ing. Dr. techn. Erich Moschik*
Zivilingenieur für Maschinenbau, A-9300 St. Veit/Glan

declares, that the system / machinery

- 1. Product:** *KLH Lifting Systems
for lifting wall and ceiling elements
consisting of lifting loops, manuf. Pewag as well as bolts*
- 2. Type:** *W 1000, W 2500, FD 1000, FD 2500, FB 1000, FB 2500*
- 3. Year of Manufacture:** *2009 / Adaptation 2021 / Adaptation 2023*
- 4. User:** *KLH Massivholz GmbH, A-8842 Teufenbach-Katsch, Gewerbestraße 4
KLH Massivholz Wiesenau GmbH, A-9400 Wolfsberg, Schwemmratten 7*

meets the following essential safety requirements and standards:

- Provisions of the EC Directives:

2006/42/EG *Directive of Machinery*

- harmonized Standards

EN 12100 -1	<i>Safety of machinery - General principles for design — Risk assessment and risk reduction</i>
EN 547-3	<i>Safety of machinery - Human body measurements</i>
EN 614-2	<i>Safety of machinery - Ergonomic design principles, Part 2: Interactions between the design of machinery and work tasks</i>
EN 818-2	<i>Short link chain for lifting purposes - Safety Part 2: Medium tolerance chain for chain slings - Grade 8</i>
EN 1492-1	<i>Textile slings - Safety Part 1: Flat woven webbing slings made of man-made fibers for general purpose use</i>
EN 13854	<i>Standards on Safety of Machinery - Minimum gaps to avoid crushing of parts of the human body</i>
EN ISO 13857	<i>Safety of machinery - Safety distances to prevent hazard zones being reached by upper and lower limbs</i>
EN ISO 14120	<i>Safety of machinery - General requirements for the design and construction of fixed and movable guards</i>
EN ISO 14123	<i>Safety of machinery - Reduction of risks to health from hazardous substances emitted by machinery</i>

<i>Originally issued</i>	<i>16.06.2012</i>
<i>Prolongation</i>	<i>01.06.2021</i>
<i>Prolongation</i>	<i>04.12.2023</i>
<i>Valid until</i>	<i>03.12.2028</i>

St. Veit/Glan, 04.12.2023



Dipl.-Ing. Dr. techn. Erich Moschik
St. Veit / Glan

The content of this declaration is in conformance with the DIN EN ISO/IEC 17050-1

EC CERTIFICATES OF CONFORMITY

DECLARATION of CONFORMITY

accord. Directive of Machinery 2006/42/EG

The Signee: *Dipl.-Ing. Dr. techn. Erich Moschik*
Zivilingenieur für Maschinenbau, A-9300 St. Veit/Glan

declares, that the system / machinery

- 1. Product:** **VLS-Visible Lifting System**
For lifting wall and ceiling elements
consisting of lifting loops, TGH rod and one-way bolts
- 2. Type:** **W2, W3, W4, W5 – wall elements**
D1, D2, D3 – ceiling elements
- 3. Year of Manufacture:** **2009 / Adaptation 2021 / Adaptation 2023**
- 4. User:** **KLH Massivholz GmbH, A-8842 Teufenbach-Katsch, Gewerbestraße 4**
KLH Massivholz Wiesenau GmbH, A-9400 Wolfsberg, Schwemmratten 7

meets the following essential safety requirements and standards:

- Provisions of the EC Directives:

2006/42/EG Directive of Machinery

- harmonized Standards

EN 12100 -1	Safety of machinery - General principles for design — Risk assessment and risk reduction
EN 547-3	Safety of machinery - Human body measurements
EN 614-2	Safety of machinery - Ergonomic design principles, Part 2: Interactions between the design of machinery and work tasks
EN 818-2	Short link chain for lifting purposes - Safety Part 2: Medium tolerance chain for chain slings - Grade 8
EN 1492-1	Textile slings - Safety Part 1: Flat woven webbing slings made of man-made fibers for general purpose use
EN 13854	Standards on Safety of Machinery - Minimum gaps to avoid crushing of parts of the human body
EN ISO 13857	Safety of machinery - Safety distances to prevent hazard zones being reached by upper and lower limbs
EN ISO 14120	Safety of machinery - General requirements for the design and construction of fixed and movable guards
EN ISO 14123	Safety of machinery - Reduction of risks to health from hazardous substances emitted by machinery

Originally issued	16.06.2012
First Prolongation	01.06.2021
Second Prolongation	04.12.2023
Valid until	03.12.2028

St. Veit/Glan, 04.12.2023



Dipl.-Ing. Dr. techn. Erich Moschik
 St. Veit / Glan

The content of this declaration is in conformance with the DIN EN ISO/IEC 17050-1

EC CERTIFICATES OF CONFORMITY

DECLARATION of CONFORMITY

accord. Directive of Machinery 2006/42/EG

The Signee: *Dipl.-Ing. Dr. techn. Erich Moschik*
Zivilingenieur für Maschinenbau, A-9300 St. Veit/Glan

declares, that the system / machinery

- 1. Product:** *VLS-S Visible Lifting System*
For lifting ceiling elements
- 2. Type:** *S1, S2, S3, S4 – ceiling elements*
- 3. Year of Manufacture:** *2021 / Adaptation 2023*
- 4. User:** *KLH Massivholz GmbH, A-8842 Teufenbach-Katsch, Gewerbestraße 4*
KLH Massivholz Wiesenau GmbH, A-9400 Wolfsberg, Schwemmratten 7

meets the following essential safety requirements and standards:

- Provisions of the EC Directives:

2006/42/EG Directive of Machinery

- harmonized Standards

EN 12100 -1	Safety of machinery - General principles for design — Risk assessment and risk reduction
EN 547-3	Safety of machinery - Human body measurements
EN 614-2	Safety of machinery - Ergonomic design principles, Part 2: Interactions between the design of machinery and work tasks
EN 818-2	Short link chain for lifting purposes - Safety Part 2: Medium tolerance chain for chain slings - Grade 8
EN 1492-1	Textile slings - Safety Part 1: Flat woven webbing slings made of man-made fibers for general purpose use
EN 13854	Standards on Safety of Machinery - Minimum gaps to avoid crushing of parts of the human body
EN ISO 13857	Safety of machinery - Safety distances to prevent hazard zones being reached by upper and lower limbs
EN ISO 14120	Safety of machinery - General requirements for the design and construction of fixed and movable guards
EN ISO 14123	Safety of machinery - Reduction of risks to health from hazardous substances emitted by machinery

Originally issued 16.06.2021
Prolongation: 04.12.2023
Valid until 03.12.2028

St. Veit/Glan, 04.12.2023



Dipl.-Ing. Dr. techn. Erich Moschik
 St. Veit / Glan

The content of this declaration is in conformance with the DIN EN ISO/IEC 17050-1

For detailed information about KLH®-Lifting systems with an EC declaration of conformity please visit www.klh.at
 The use of other lifting equipment with an EC Declaration of Conformity may only be used in accordance with the valid operating instructions of the respective manufacturer.
 Please observe the country-specific safety regulations for all systems and ensure that the prescribed personal protective equipment and construction site equipment are used.



KLH MASSIVHOLZ GMBH

Gewerbestraße 4 | 8842 Teufenbach-Katsch | Austria

Tel +43 (0)3588 8835 | Fax +43 (0)3588 8835 415

office@klh.at | www.klh.at